

pitertools - Bug #5313

PITR archiving bug

05/14/2015 03:39 PM - Michael Vitale

Status:	Closed	Start date:	05/14/2015
Priority:	Normal	Due date:	
Assignee:	Eric Worden	% Done:	0%
Category:		Estimated time:	0.00 hour
Target version:			
Resolution:	fixed		

Description

In the cmd_archiver.ini file, if you don't specify the remote copy archive location with a trailing forward slash at the end, when you start to do WAL archiving, files will be created in the data directory of the slave, and the archive subdirectory will not be created. There is no such problem with or without the trailing forward slash for the local archive directory, l_archivedir.

To simulate the problem, set r_archivedir without a trailing slash, and make sure the \$PGDATA/archive directory does not exist on the slave.

```
r_archivedir: /var/lib/postgresql/9.3/main/archive
```

To get it to run as expected, add the trailing slash and repeat the tests. Things work fine this way:

```
l_archivedir: /var/lib/postgresql/9.3/main/archive/
```

History

#1 - 10/22/2015 11:03 AM - Eric Worden

- Status changed from New to Closed
- Assignee changed from Michael Vitale to Eric Worden
- Resolution set to fixed

This issue affects the version in the tarball referenced in the wiki but not the current HEAD of master.

Eric